

Devon Strait

Geared Cellular Container Vessel

Deadweight : 13.760 mt on scantling draft of 8,50 m ssw
10.400 mt on design draft of 7,30 m ssw

Container intake : total 1.118 TEU
in holds 334 TEU
on deck 784 TEU

Flag : Liberia

Shipyard : Jingling Shipyard, China

Built : March 2008

Class : DNV

Speed : about 19,5 knots

Main Details

LOA : 148,00 m
LBP : 140,30 m
Beam : 23,25 m
Depth : 11,50 m

Container Capacities

Container intake basis 14ts homogenous load: 712 TEU

| Highcube intake | : | TEU | or | FEU | Tiers |
|-----------------|---|-----|----|-----|-------|
| Hold No. 1 | | 8 | | 4 | 1 |
| No. 2 | | 14 | | 7 | 2 |
| No. 3A | | 28 | | 14 | 2 |
| No. 3B | | 28 | | 14 | 2 |
| No. 4A | | 28 | | 14 | 2 |
| No. 4B | | 28 | | 14 | 2 |
| No. 5 | | 28 | | 14 | 2 |

Reefer plugs : total 220 whereof 164 reefer plugs on deck and 56 in holds.

Permissible Stackweights:

| | 20' | 40' | 45' | 48' |
|---------|--------|------|-----|-----|
| Hold | : 120t | 150t | | |
| Deck | : 65t | 80t | 80t | 80t |
| Hatches | : 50t | 80t | 80t | |

Gear

2 cranes of 45mt

Hatch covers

Pontoon hatch covers, non-sequential are arranged on main deck for No.1) hatch with one cover, No. 2) to 5) hatches with 2 covers each.

Hatch dimensions :

No. 1 : 14,00 m x 10,40 m

No. 2 - 5 : 12,60 m x 18,00 m

Machinery

Main Engine : MAN 7L58/64 of 9730 kw/428 rpm

Auxiliary Engines : 3 x MAN B&W ZJMD 6L16/24 each 590kw/1200 rpm

Bowthruster : 700 kw, JASTRAM

All details are given in good faith and are about but without guarantee.